

CARE & MAINTENANCE INSTRUCTIONS

These instructions apply to BerryAlloc Kitchen Wall.

1. Area of use

BerryAlloc Kitchen Wall is an interior panel to be installed on existing walls in domestic and public environments. BerryAlloc Kitchen Wall is mainly designed to be used in dry or wet kitchen areas (e.g. between the countertop and the wall cabinets).

2. Care

BerryAlloc Kitchen Wall is an easy-care interior wall plate with a long lifespan and a hygienic surface.

To prolong the life of the wall panel, it is however necessary to take precautions against unnecessary loads on the surface to avoid scratches.

Indoor temperature and relative air humidity

The BerryAlloc Kitchen Wall interior panel is produced from wood fibre material that reacts on changes in the indoor climate. The ideal indoor climate for a wall panel is a relative humidity of between 40 and 60 % and a temperature of between 19 and 24 °C. If the humidity in the air becomes too low, the wall panel may dry on one side and because of this change its dimensions.

3. Regular maintenance

Cleaning

Use a damp microfiber cloth and water. Where detergents are to be used in the water, synthetic detergents should be used. Organic detergents leave behind a thin film of grease on the surface and will result in visible stains on the surface.

Use, in areas with high water exposure, a detergent made for eliminating calcium.

NB: Never use abrasive cleaning methods (abrasive detergents/scrubs) on the BerryAlloc Kitchen Wall interior panel!

Stubborn stains can be wiped off with a slightly damp cloth and methylated or white spirit. If BerryAlloc Kitchen Wall interior panels with tile design are subjected to spills from chemicals (with corrosive substances), the spills must be removed immediately. Otherwise there might appear slight colour differences in the grout lines of the panels.

Cured adhesive/sealant on the edges of the BerryAlloc Kitchen Wall interior panels can after installation easily be removed with a plastic scraper and cleaned with white spirit.

Removability

The BerryAlloc Kitchen Wall interior panels can be removed but normally not reinstalled. Therefore, it is possible to replace damaged panels.

Disposal of any waste material must take place in accordance with the material safety datasheet (MSDS) for BerryAlloc Kitchen Wall (www.berryalloc.com).

4. Transport and storage

BerryAlloc Kitchen Wall is protected by perforated shrink wrap. This means that the packages may be transported without temperature restrictions, but the packages are to be stored in temperatures above the freezing point and protected from rain, snow and long-term bright light. We also recommend storing and transporting them horizontally. The packages should be protected from shocks along the edges.

5. Health and environment

BerryAlloc Kitchen Wall has been tested according to national and European standards for emission and toxicity and it is recommended by the Norwegian Asthma and Allergy Association (NAAF).



The product has been tested and approved by a number of European fire test laboratories.

6. More information

For further information on BerryAlloc Kitchen Wall or other products supplied by BerryAlloc, please see BerryAlloc brochure material or visit our website: www.berryalloc.com.